

ST400i Stapler

Features

Impulse Technology

- Portable, no need for compressors or air lines
- Fast, high output design
- Drives up to 2 staples per second
- Five times faster than manual staple placement

Ergonomic Design

- Comfort for periods of high use
- Hose free (cordless) for work in remote situations

Adjustable Depth of Drive

- Greater flexibility for staple placement and a superior finish
- Prevents damage to wire

Suitable for 40, 45 and 50mm Length Staples

- Ideal for rural wire to post fencing applications

Suitable for 4.0mm Diameter Staples

Quick Clear Nose

- Less downtime if fastener jams occur

Top Load Magazine

- Easy and fast re-loading

Sequential Trigger System

- Improved operator safety

V-Notch Guide and Angle Wire Guide Attachments

- Ensures fast, accurate, staple placement while protecting wire

Staple Lock-out Bar

- Protects tool and wire from misfire damage



Product Code	Description	Barcode
ST4iAP1	STOCKade 4.0mm Stapler	9315104016996

ST400i Stapler

Specifications	ST4iAP1
Product Size (WxHxD)	110 x 370 x 430mm
Packaged Size (WxHxD)	160 x 470 x 510mm
Tool Weight (with battery)	4.2kg
Packaged Weight	8.0kg
Quantity Per Pack	1
Cycle Rate Per Second	2 staples per second
Magazine Capacity (Short)	50 staples (approx 2 strips)
Battery Capacity (Maximum)	More than 3,000 staples per charge
Fuel Cell Capacity	More than 500 staples per cell
Staple Range Length	40, 45 and 50mm
Staple Diameter	4.0mm
Staple Type	Divergent point (hot dipped galvanised)
Battery	3.7V DC
Battery Recharge	1.5 hours
Fuel Cell Propellant	STOCK-ade Impulse Fuel Cell Liquid Hydrocarbon
Fuel Cell & Battery Operating Temperature	-15° to 49°C (5° to 120°F)
Rated Input Voltage Battery Charger	100-240V 50/60Hz AC or 10-16V DC
Rated Output Voltage Battery Charger	3.7V 2.1A

Applications	
	Rural livestock fencing
	Horticulture
	Rural heavy mesh and heavy woven fencing
	Predator control fencing
	Highway boundary fencing
	Rural utilities applications

The information presented in this product information sheet is correct as at the date of publication. STOCK-ade reserves the right to change performance, product or content information without notice.
READ ALL SAFETY INSTRUCTIONS