

Overview

LHT15/158/8 is a lightweight, high tensile poultry net with closely spaced vertical stay wires, ideal for short to medium term projects. Tornado LHT Poultry Fence is manufactured with high tensile wire which strains tighter than mild steel and so requires fewer intermediate posts, making it quicker to erect. It does not stretch with weathering so does not need to be retightened annually.

Compliance with British and European Standards

BSEN 10218 - Steel Wire and Wire Products part 2 - General Wire Dimensions and Tolerances.
 BSEN 10223 - Steel Wire and Wire Products for Fencing and Netting part 5 - Steel Wire Woven Hinged Joint and Knotted Mesh Fencing.
 BSEN 10244 - Steel Wire and Wire Products Non-ferrous Metallic Coatings on Steel Wire part 2 - Zinc or Zinc Alloy Coatings (all Tornado products galvanised to class A).

Sustainability

All Tornado products are 100% recyclable.

Traceability

This fence is batch marked and can be traced back to point of manufacture.

Installation Guidelines

A straining post is required at every major change in direction or any termination and should be supported by a strut or box assembly. Netting should be tied off on the straining posts by hand or with suitable joiners. When tensioning the fence the 'crimp' in the net should be reduced by approx: 50%. Avoid driving staples tight against the wire as this will damage the galvanised coating. A single electrified wire can be used as an additional deterrent for fox exclusion, and the bottom of the net can be turned out.

Health and Safety

It is recommended that safety gloves, boots and glasses are worn at all times when handling the product.

Suitable for

- Poultry & Wild Fowl
- Kennels

Specification

No. of Line Wires	15
Overall Height (cm)	158
Distance between stay wires (cm)	8
Top & bottom line wire specification	2mm dia - 1235-1390 N/mm ²
Intermediate line wire specification	2mm dia - 1235-1390 N/mm ²
Vertical stay wire specification	2mm dia - 695-850 N/mm ²
Average Weight per 50 Metre Roll (kg)	56
Material Composition	Heavily galvanised steel wire

Product Codes

HZLH151502	30 metre roll
HZLH151501	50 metre roll
HZLH151503	100 metre roll

All measurements are approximate. It is the user's responsibility to check the product is suitable for the application. We reserve the right to change specifications without notification.

